

	IP61	IP64 (new)
		
Physical	Size: 133 x 53 x 24 mm Colour: Black Display: FSTN B/W 28 x 35 mm 112 x 115 pixel White LED backlight	Size: 137 x 52 x 21.5 mm Colour: Black Display: High resolution Colour LCD display 28 x 35 mm 1,8 inch White LED backlight
Buttons & Keys	3 function keys On hook, power on / hook off 4 direction navigation Numeric block Volume + and - Ringtone on / off	3 function keys On hook, power on / hook off 4 direction navigation Numeric block Volume + and - Ringtone on / off
Battery	Type: Li-Ion Speech time: 16 h Charge time: <4 h	Type: Li-Ion Speech time: 16 h Charge time: <4 h
Interfaces	Headset interface (Standard 2.5 mm)	Headset interface (Standard 3.5 mm)
Radio	Frequency range: 1880-1900 MHz Modulation: GFSK Antenna: Integral Sensitivity: -93 dBm Dynamic output power: 10 mW (EU)	Frequency range: 1880-1900 MHz Modulation: GFSK Antenna: Integral Sensitivity: -93 dBm Radiated power: 250 mW (EU)
Environmental	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Enclosure protection: IP40	Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Enclosure protection: IP40, IEC EN60529
Order number	50-00061-001	50-00064-004